



SNIPER & SNIPER K

New internals delivering better durability and enhanced shooting experience. The valve and valve stem have been reworked to be more efficient. The trigger system is refined to provide smooth trigger pull. The rear butt plate has been upgraded.

Caliber	.177, .22, .25, .30, .35, .45, .50
Action System	Side lever action
Barrel	Rifled (choked or unchoked)
Barrel Length	.177, .22, .25 : 400 ~480mm, .30, .35, .45,.50 : 500~550mm
Recommended ammo in Grains	22 : 18 ~ 26 grain, .25 : 25 ~ 32 grain, .30 : 44 ~50 grain, .35 : 80~100grain, .45 : 180 grain, .50 : 180~210 grain
Max Ammo Length	177~.25 : 9.8mm, .30~.50 : 14.5mm
Overall Length	1040 ~1170mm
Cylinder Size	280cc (carbon steel cylinder)
Barrel Twist Rate	1:19
Front Sight	none
Rear Sight	none
Scopeable	22mm Picatinny rail
Trigger	Two-stage adjustable
Working pressure	250bar ~ 80bar
Suggested for	Hunting
Thread	1/2 unf, 5/8"-18 unf (.30) ? (.35 - .45-.50) :M22
Color	Black
Safety	Manual
Fixed/adj. power	Fix
Function	Side lever action, Mag Fed, Repeater
Weight	3.7kg
Stock	Metal & Synthetic (length & height adjustable stock)

Caliber	Grain Weight	FPS	FPE
0.30	50.15	1004	112
0.35	81.02	928	155
0.45	180	756	228
0.50	210	758	268